

Model1100M Series

10/100M Managed Ethernet Media Converter

Features

1. Accord to IEEE802.1 10Base-T, IEEE802.3u 100Base-TX, IEEE802.3 100Base-FX
2. MDI/MDI-X auto negotiation, 10M/100M auto negotiation
3. Supports full /half duplex, Point-to-point transparent transfer
4. Support WEB, SNMP, TELNET management, upgraded online via TFTP
5. The module must be inserted into 2U 19", 17 slots Rack mount, RACK2000C
6. Manageable stand-alone media converters in remote end



Introduction

Model1100M series, 10/100M remote manageable fiber media converters offer a high price/performance ratio; cover all functions of non-manageable fiber media converter including variety of data rate, SM/MM, single fiber and double fiber etc. with simple set-up and

complete function management interface, it supports protocols such as HTTP,SNMP,TFTP,TELNET ...etc, and realizes the integrated management to all chassis.

Manageable functions

View manageable system supports full range of standards such as HTTP,SNMP,TFTP,TELNET ...etc . The system has proper interface for each.

1. Support WEB based management

Our manageable system supports the management based on WEB. It is easy to be understood and used, no need install special software, so that it is easier for the users.

2. Support SNMP management

Fully support SNMP, the users can manage the relational devices via any operating system, such as HP-OpenView .

3. Support Console management when emergency

Support local command-string management via Console port , the users can manage the devices via other networks such as Telephone System , in case the Ethernet networks failed .

4. Support TELNET

5. The software can be upgraded online via TFTP.

Specifications

Standards: comply with IEEE802.1 10Base-T, IEEE802.3u 100Base-TX, IEEE802.3 100Base-FX

Console port: RS232(RJ45)

RJ45 port rate: 10/100Mbps auto negotiation

Optic port rate: 100Mbps

Working: Asynchronous, point to point

Transfer distance: RJ45port: 100m

Fiber optic:20,40,60,80,100,120km(SM),
2 km(MM) optional

RJ45 port cable: UTP 5E

Fiber connector: SC, ST, FC optional

Fiber optic cables: Single Mode:8.3/125,8.7/125,9/125 or 10/125 um

Muti-Mode:50/125,62.5/125 um

Wavelength:850nm,1310nm,1550nm

Power

Power supply: External 5VDC input

Consumption: 4W

Environment

Operating temp:-10°C to 65°C

Storage temperature: -20 to 70°C

Operating humidity: 5% to 95%(no condensation)

Appearance

Dimensions: 94.0×71.0×26.0mm(stand-alone)

Shell: Iron

Color: White

Weight: 230g(power external)

Warranty: 5 years

Approvals: FCC,CE, RoHS approvals

Ordering information

Model NO.	Description
Model1100M	multi-mode, 2Km, 5VDC, SC, FC or ST, optional, managed
Model1100MS/20	single-mode, 20Km,5VDC, SC, FC or ST, optional, managed
Model1100MS/40	single-mode, 40Km, 5VDC, SC, FC or ST, optional, managed
Model1100MS/60	single-mode, 60Km, 5VDC, SC, FC or ST, optional, managed
Model1100MS/80	single-mode, 80Km, 5VDC, SC, FC or ST, optional, managed
Model1100MS/100	single-mode, 100Km,5VDC, SC, FC or ST, optional, managed
Model1100MS/120	single-mode, 120Km, 5VDC, SC, FC or ST, optional, managed
Model1100MSS/20	single-mode, single fiber, 20Km, 5VDC, SC, FC or ST, optional, managed
Model1100MSS/40	single-mode, single fiber, 40Km, 5VDC, SC, FC or ST, optional, managed
Model1100MSS/60	single-mode, single fiber, 60Km, 5VDC, SC, FC or ST, optional, managed
Model1100MSS/80	single-mode, single fiber, 80Km, 5VDC, SC, FC or ST, optional, managed
Model1100MC	multi-mode, 2Km, SC, FC or ST, optional, managed, card
Model1100MCS/20	single-mode, 20Km, SC, FC or ST, optional, managed, card
Model1100MCS/40	single-mode, 40Km, SC, FC or ST, optional, managed, card
Model1100MCS/60	single-mode, 60Km, SC, FC or ST, optional, managed, card
Model1100MCS/80	single-mode, 80Km, SC, FC or ST, optional, managed, card
Model1100MCS/100	single-mode, 100Km, SC, FC or ST, optional, managed, card
Model1100MCSS/20	single-mode, single fiber, 20Km, SC, FC or ST, optional, managed, card
Model1100MCSS/40	single-mode, single fiber, 40Km, SC, FC or ST, optional, managed, card
Model1100MCSS/60	single-mode, single fiber, 60Km, SC, FC or ST, optional, managed, card
Model1100MCSS/80	single-mode, single fiber, 80Km, SC, FC or ST, optional, managed, card